




Xmitter Prime Xtreme double Stack led Light bar



The Xmitter Prime Double Stack features 4 rows of 5 watt LED to provide powerful output. Making this this most powerful light bar per inch.

Xmitter Prime Extreme Features

- > Weatherproof Deutsch Connector with Plug and Play Harness
- > Integrated Electronic Thermal Management
- > Billet Clamp Tube Frame Mounts Available
- > Next Gen LED Is Driven to 90% Efficiency
- > PWM Integrated Dimming Circuitry
- > Extruded 6061 Aluminum Housing
- > Advanced Heat Sink Design
- > Polycarbonate Lens
- > Patent # US 7,950,821 B1

Billet Tube Frame Mounts

360° Tube Frame Mount System
TUBE MOUNTS
Machined Billet Clamps fit all Xmitter Series Light Bars for tubed frame or chassis mounting.



XIL-B175 (45mm) Shown
Features

- > Machined Billet 6061 Aluminum
- > Includes All Mounting Hardware
- > Laser Engraved Vision X Logo
- > Sold In Pairs
- > Diameter: 19mm - 25mm - 32mm - 38mm - 43mm - 45mm - 51mm

Xmitter Prime Xtreme Series Usage Guide

5 WATT XTREME LIGHTING

The Xmitter Prime uses 5 Watt LED for the combination of the most distance and most intense light output.

PRIME DRIVE TECHNOLOGY

With Prime Drive, Electronic Thermal Management maintains a safe operating temperature for the light without sacrificing output.

DIMMING CAPABILITY

Pulse Width Modulation circuitry flashes the LED faster than the human eye can see to achieve dimming capability.

EXTRUDED ALUMINUM

Extruded 6061 Aluminum is used to achieve an Ingress Protection rating of IP-68, creating a light bar with unmatched durability.

PART#	Beam Pattern	Raw Lumens	Dimensions	Weight	Wattage
XIL-PX2.610	10° Narrow	6,336 lm(ea)	120/123.1/83.8 mm	2.1 kg	60 Watt
XIL-PX2.640	40° Wide	6,336 lm(ea)	120/123.1/83.8 mm	2.1 kg	60 Watt
XIL-PX2.1210	10° Narrow	12,672 lm(ea)	201/123.1/83.8 mm	3.7 kg	120 Watt
XIL-PX2.1240	40° Wide	12,672 lm(ea)	201/123.1/83.8 mm	3.7 kg	120 Watt
XIL-PX2.1810	10° Narrow	19,008 lm(ea)	282/123.1/83.8 mm	4.5 kg	180 Watt
XIL-PX2.1840	40° Wide	19,008 lm(ea)	282/123.1/83.8 mm	4.5 kg	180 Watt
XIL-PX2.3010	10° Narrow	31,680 lm(ea)	444/123.1/83.8 mm	6.1 kg	300 Watt
XIL-PX3040	40° Wide	31,680 lm(ea)	444/123.1/83.8 mm	6.1 kg	300 Watt
XIL-PX2.3610	10° Narrow	38,016 lm(ea)	525/123.1/83.8 mm mm	6.9 kg	360 Watt
XIL-PX3640	40° Wide	38,016 lm(ea)	525/123.1/83.8 mm mm	6.9 kg	360 Watt

