




Xmitter Prime Xtreme
Single Stack led Light bar



Xtreme Output for Increased Distance and Spread

The Xmitter Prime Xtreme is the newest generation of the original Xmitter Bar packed with new technology. It features Prime Drive for electronic thermal management and dimming capability. 5 Watt LEDs increase light output to 528 lumens per LED.

Xmitter Prime Xtreme Series Usage Guide

5 WATT XTREME LIGHTING

The Xmitter Prime uses 5 Watt LED for the combination of the most distance and most intense light output.

PRIME DRIVE TECHNOLOGY

With Prime Drive, Electronic Thermal Management maintains a safe operating temperature for the light without sacrificing output.

DIMMING CAPABILITY

Pulse Width Modulation circuitry flashes the LED faster than the human eye can see to achieve dimming capability.

EXTRUDED ALUMINIUM

Extruded 6061 Aluminium is used to achieve an ingress Protection rating of IP-68, creating a light bar with unmatched durability.

PART#	Beam Pattern	Raw Lumens	Dimensions	Weight	Wattage
XIL-PX610	10° Narrow	3,168 lm(ea)	120/95.25/84.07 mm	1.2 kg	30 Watt
XIL-PX640	40° Wide	3,168 lm(ea)	120/95.25/84.07 mm	1.2 kg	30 Watt
XIL-PX1210	10° Narrow	6,336 lm(ea)	201/95.25/84.07 mm	2.4 kg	60 Watt
XIL-PX1240	40° Wide	6,336 lm(ea)	201/95.25/84.07 mm	2.4 kg	60 Watt
XIL-PX1810	10° Narrow	9,504 lm(ea)	282/95.25/84.07 mm	3 kg	90 Watt
XIL-PX1840	40° Wide	9,504 lm(ea)	282/95.25/84.07 mm	3 kg	90 Watt
XIL-PX3010	10° Narrow	15,840 lm(ea)	444/95.25/84.07 mm	4.5 kg	150 Watt
XIL-PX3040	40° Wide	15,840 lm(ea)	444/95.25/84.07 mm	4.5 kg	150 Watt
XIL-PX3610	10° Narrow	19,008 lm(ea)	525/95.25/84.07 mm	4.8 kg	180 Watt
XIL-PX3640	40° Wide	19,008 lm(ea)	525/95.25/84.07 mm	4.8 kg	180 Watt
XIL-PX5410	10° Narrow	28,512 lm(ea)	768/95.25/84.07 mm	6.6 kg	270 Watt
XIL-PX5440	40° Wide	28,512 lm(ea)	768/95.25/84.07 mm	6.6 kg	270 Watt
XIL-PX7210	10° Narrow	38,076 lm(ea)	1011/95.25/84.07 mm	8.4 kg	360 Watt
XIL-PX7240	40° Wide	38,076 lm(ea)	1011/95.25/84.07 mm	8.4 kg	360 Watt
XIL-PX9010	10° Narrow	47,520 lm(ea)	1254/95.25/84.07 mm	10.2 kg	450 Watt
XIL-PX9040	40° Wide	47,520 lm(ea)	1254/95.25/84.07 mm	10.2 kg	450 Watt



Xmitter Prime Extreme Features

- ▶ Weatherproof Deutsch Connector with Plug and Play Harness
- ▶ Integrated Electronic Thermal Management
- ▶ Billet Clamp Tube Frame Mounts Available
- ▶ Next Gen LED is Driven to 90% Efficiency
- ▶ PWM Integrated Dimming Circuitry
- ▶ Extruded 6061 Aluminum Housing
- ▶ Advanced Heat Sink Design
- ▶ Polycarbonate Lens
- ▶ Patent # US 7,950,821 B1

Xmitter Prime Polycarbonate Covers

Polycarbonate covers help protect against rocks and oncoming debris as well as increased visibility in fog. With easy snap on installation.



PCV-P12BL Shown
PCV-P12Y Shown
Features

- ▶ Shatterproof Polycarbonate Protects from Rock and Debris Impact
- ▶ Black for Street Legal Use Where Applicable
- ▶ Yellow Covers to Penetrate Fog

Billet Tube Frame Mounts

360° Tube Frame Mount System

TUBE MOUNTS
Machined Billet Clamps fit all Xmitter Series Light Bars for tubed frame or chassis mounting.



XIL-B175 (45mm) Shown
Features

- ▶ Machined Billet 6061 Aluminum
- ▶ Includes All Mounting Hardware
- ▶ Laser Engraved Vision X Logo
- ▶ Sold in Pairs
- ▶ Diameter: 19mm - 25mm - 32mm - 38mm - 43mm - 45mm - 51mm

