



Xmitter Prime Iris R

Iris Reflectors For Ultimate Distance



IRIS reflector technology

Vision X Lighting introduces the Xmitter Prime Iris Light Bar series or XPR. This new generation of LED light bars features two features not seen on a Vision X light bar before, IRIS reflector technology, and dual mounting, both patented feet mount and end mount brackets are included standard. The XPR series is launching with 7 different lengths, ranging from 11.5\"/>

The 10-watt LEDs in these light bars are paired with IRIS reflector technology to project usable light further than ever before possible. IRIS reflector technology was first introduced with the Optimus Series in 2012, using deeply recessed reflectors to achieve unmatched distance in a light of that size.

The XPR light bars create an unmatched distance option in LED Light Bars. The 27 LED light bar produces 1,600ft of usable light. Another new innovation in these light bars is the use of tilting reflectors, allowing the outer 3 LEDs on each end of the light bars (sizes above 6 LED) to tilt out to create a mixed or combo beam pattern. Increasing the spread of the light, tilting reflectors creates even more visibility for the driver.

The XPR series offers several mounting options, Vision X's patented feet mounts, new end mount brackets, or pair the patented feet mounts with Vision X's billet tube mounts (available as an accessory) to mount to roll cages or any tube framing. New end mounts securely fasten to the housing with two bolts and lock washers per end, and allow for vertical adjustment once mounted.



| PART# | Beam Pattern | Raw Lumens | Dimensions | Amp Draw | Wattage |
|---------|--------------|---------------|-----------------------|----------|----------|
| XPR-3 | Straight | 3,237 lm(ea) | 22.2/80.01/81.02 mm | 2.5A | 30 Watt |
| XPR-6 | Straight | 6,474 lm(ea) | 29.2/1/80.01/81.02 mm | 5A | 60 Watt |
| XPR-9 | Tilted | 9,711 lm(ea) | 500/80.01/81.02 mm | 7.5A | 90 Watt |
| XPR-12M | Tilted | 12,948 lm(ea) | 609.6/69/76.25 mm | 10A | 120 Watt |
| XPR-15M | Tilted | 16,185 lm(ea) | 746.76/69/76.25 mm | 12.5A | 150 Watt |
| XPR-18M | Tilted | 19,422 lm(ea) | 881.38/69/76.25 mm | 15A | 180 Watt |
| XPR-21M | Tilted | 22,659 lm(ea) | 1016/69/76.25 mm | 17.5A | 210 Watt |
| XPR-24M | Tilted | 25,896 lm(ea) | 1150/69/76.25 mm | 20A | 240 Watt |
| XPR-27M | Tilted | 29,133 lm(ea) | 1285.24/69/76.25 mm | 22.5A | 270 Watt |



Xmitter Prime Iris R Features

- ▶ Dual Mounting Options Standard (patented feet mount or end mount)
- ▶ Proprietary IRIS Reflector Technology Featuring Tilting Reflectors
- ▶ Tilting Reflectors Provide Mixed/Combo Beam Spread
- ▶ Xtreme Five Watt LED is Driven to 90% Efficiency
- ▶ Integrated Electronic Thermal Management
- ▶ Weatherproof Deutsch Connector
- ▶ Polycarbonate Lens
- ▶ Patent Pending



Xmitter Polycarbonate Covers

Polycarbonate covers help protect against rocks and oncoming debris as well as increased visibility in fog. With easy snap on installation.



PCV-P12BL Shown
PCV-P12Y Shown
Features

- ▶ Shatterproof Polycarbonate Protects from Rock and Debris Impact
- ▶ Black for Street Legal Use Where Applicable
- ▶ Yellow Covers to Penetrate Fog

Billet Tube Frame Mounts

360° Tube Frame Mount System

TUBE MOUNTS

Machined Billet Clamps fit all Xmitter Series Light Bars for tubed frame or chassis mounting.



XIL-B175 (45mm) Shown
Features

- ▶ Machined Billet 6061 Aluminum
- ▶ Includes All Mounting Hardware
- ▶ Laser Engraved Vision X Logo
- ▶ Sold in Pairs
- ▶ Diameter: 19mm - 25mm - 32mm - 38mm - 43mm - 45mm - 51mm

